

# HOW TO INSTALL YOUR CONCEALED TIEBACK HOLDER

(Designed to be used with Fabric Tiebacks)

YOUR TIEBACK HOLDER WILL REDUCE WRINKLES AND END FOLD DISTORTIONS.

**SECTION A**

**SECTION B**

4 <sup>7</sup>/<sub>8</sub>" - 7 <sup>3</sup>/<sub>4</sub>"

WITHOUT TIEBACK  
Drapery Folds Overlap  
And Bunch Together

WITH TIEBACK  
Drapery Folds Are  
Neat And Straight

Join sections (A) and (B) with screws and nuts provided. Holder is adjustable from 4 <sup>7</sup>/<sub>8</sub>" - 7 <sup>3</sup>/<sub>4</sub>". Determine projection of drapery return to wall and set tieback holder to same depth. The holdback can be cut down for less depth and spacers can be used for more depth.

**STANDARD INSTALLATION**

**ALTERNATIVE INSTALLATION**  
Allows tieback to drop further down on drapery yet still rest on holder.

Locate tieback holder on wall or casing at height desired. If it is not possible to install tieback holder with screws in casing, use proper wall anchors in wall.

**TOP VIEW OF CONCEALED HOLDER**

DRAPERY

WINDOW CASING

DRAPERY HOOK

RETURN

TIEBACK

TIEBACK HOLDER

**TIEBACKS WITH RINGS ATTACHED ON ENDS.**

TABS

DRAPERY FOLDS

Slip the tieback ring over the tab on top of tieback holder. Wrap tiebacks around drapery folds and slip tieback ring over tab in middle of holder.

**TIEBACKS USING PIN-ON HOOKS**

HOOK NOTCH

HOOK HOLE

Pin hook through tiebacks and into hook hole in top of holder. Wrap other end of tieback with hook around drapery folds and hook into notch on top of holder.